

EVMOTIONS Delta EVSE Type2 (3x16A) EV Charger



Electric car EV charger Type2 industrial red with 3 x 16A connector (11kW) + Carrying bag + Wall mount

- Electric car battery charger
- Free car carrying case and wall mount!
- Charging delay function (maximum 10 hours)
- Standard battery charger for electric cars with Type2 connection
- LCD display, displays the current charging current, temperature and power consumption
- IP65 protection level (Protected against dust, Protected against splashing water from all directions)
- 1. Mennekes (Type-2)
- 2. CEE 3x16A industrial red (diameter: 56mm)
- Cable length: 5 meters
- Number of phases: 3
- Current per phase: 8-10-13-16 A (variable)
- Memorizes the current used during the last charge, no need to set it for each charge
- Max. power: 11 kW
- Charging side connector: CEE 3x16A industrial red
- Car side connector: Type 2 - IEC 62196
- The cable has TÜV, CE, UL approvals.
- This charging station has overcurrent protection, overvoltage protection, leakage protection and overheating protection
- This cable can be used to charge electric cars equipped with Type2 connectors at home (as long as there is a CEE 3x16A industrial socket).
- Cable thickness: $5 \times 2.5 \text{ mm}^2 + 1 \times 0.5 \text{ mm}^2$
- Compatible with the following popular car models, among others:
 - Audi | BMW | BYD | Chevrolet (EU) | Cupra | Dacia | Dongfeng | DS | Fiat | Ford | Honda | Hongqi | Hyundai | Jaguar | JEEP | Kia | Land Rover | Lancia | Leapmotor | Mazda | MG | Nissan |



Mercedes | MG | Mini | Mitsubishi | Omoda | Opel | ORA | Peugeot | Polestar | Porsche | Renault | SMART | Skoda | Suzuki | Tesla (EU) | Toyota | Volvo | Volkswagen | XPENG ...

- Power source: 400V
- Dimensions: 100 x 6000 x 84 mm
- Weight: 2.65 kg