

EVMOTIONS Lambda EVSE Type2 (max. 16A) EV Charger



Electric car EV charger Type2 1 phase (3.7kW) 8 meters + Carrying bag

- Electric car battery charger
- Charging delay function (maximum 10 hours)
- Standard battery charger for electric cars with Type2 connection
- LCD display, displays the current charging current, temperature and power consumption
- IP65 protection level (fully protected against dust and protected against low-pressure water jets from all directions)
- 1. Mennekes (Type-2)
- 2. Schuko 230V Standard mains plug
- Cable length: **8 meters**
- Number of phases: 1
- Current per phase: 6-8-10-13-16 A (variable)
- Memorizes the current used during the last charge, no need to set it for each charge
- This charging station has overcurrent protection, overvoltage protection, leakage protection and overheating protection
- Max. power: 3.7 kW
- Charging side connector: 230V standard
- Car side connector: Type 2 - IEC 62196
- The cable has TÜV, CE, UL approvals.
- Overheating protection built in
- This cable can be used to charge an electric car equipped with a Type2 connector at home
- Cable thickness: $3 \times 2.5 \text{ mm}^2 + 1 \times 0.5 \text{ mm}^2$
- Compatible with the following popular car models, among others:
- Audi | BMW | BYD | Chevrolet (EU) | Cupra | Dacia | Dongfeng | DS | Fiat | Ford | Honda | Hongqi | Hyundai | Jaguar | JEEP | Kia | Land Rover | Lancia | Leapmotor | Mazda | MG | Nissan | Mercedes | MG | Mini | Mitsubishi | Omoda | Opel | ORA | Peugeot | Polestar | Porsche | Renault |



SMART | Skoda | Suzuki | Tesla (EU) | Toyota | Volvo | Volkswagen | XPENG ...

- Power source: 230V
- Dimensions: 100 x 6000 x 84 mm
- Weight: 2.2 kg